

This Engine Warranty covers defects in parts and workmanship for:
(24) Months on Turn Key Engines Broken in on Run-Up Stand
(12) Months on Long Block Engines
(6) Months on Short Block Engines.

WARRANTY STATEMENT

This limited warranty does NOT cover any labor or installation/removal costs on any warranty claims submitted to The Motor Pool USA LLC. This warranty is strictly limited to repairs, rebuilding or replacement of a defective engine. The Motor Pool USA LLC is not responsible for any vehicle damage due to our products. The Motor Pool USA LLC is NOT responsible to make road service calls to examine or troubleshoot an engine with a problem. If a problem exists, the engine must be removed and returned to The Motor Pool USA LLC in the condition as sold for examination. This warranty begins to run on the date of the original final invoice and any repairs or replacements shall not extend this warranty. This warranty is non-transferable.

THIS WARRANTY DOES NOT COVER:

- Damage due to improper installation, negligence, alteration (including changes to engine controls), accident, or improper use. Proper vehicle use is discussed in the Vehicle Owner's Manual.
- Damage caused by Improper Break-In or lack of proper maintenance. Failure to follow provided break-in Instructions or Maintenance Schedule intervals, or failure to use or maintain proper type and levels of fluid, fuel, oil, and lubricants. Proof of proper maintenance is the owner's responsibility. Keep all receipts and be prepared to present them if questions arise about maintenance.
- Any vehicle that has been used for racing (on or off track), stunt driving, performance testing, or used under other extreme operating conditions
- Damage as a result of overheating, contamination or lack of lubrication.
- Damage caused by customer provided parts or addition of a turbocharger, supercharger, or nitrous oxide.
- Damage as a result of modification / replacement of torque converter that is part of transmission assembly or use of engine in excess of maximum torque specification.
- Oils & Fluids or Damaged/Worn out Accessories and Equipment.
- Loss of time, inconvenience, loss of use, or other economic loss.
- Vehicles registered and normally operated outside of The United States.

EXPRESS AND IMPLIED WARRANTY DISCLAIMER

The Motor Pool USA LLC disclaims all warranties, express or implied. Other than the terms and provisions of this limited warranty, no other warranty is expressed or implied. This sale carries no implied warranties of merchantability or fitness for a particular use or purpose.

Customer Print Name _____

Final Invoice Date _____

I have carefully read through this Limited Warranty, and I understand and agree to all the terms and conditions that apply.

Signed _____ Date _____

Thank you for your purchase. If we can provide any information about our products or company, please call the Motor Pool USA LLC at 928-259-3216 or Contact Us on our Website www.themotorpoolaz.com

Engine Break-In

- 1 We Recommend Using Amsoil SAE 30 Break-In Engine Oil- We Sell in Shop.**
- * Add **ZZDP Zinc Additive** to SAE 30 Oil if Not Using Amsoil Products
- ******DO NOT Use Synthetic Engine Oil******
- 2 Use Only Water in Cooling System** instead of Coolant for Break-In Period.
- 3 Ensure all Accessories/Belts/Hoses Exhaust Bolts, etc. are Tight**
- 4 Ensure Proper Spark Plug Gap and Plug Wire Firing Order is Correct.**
- 5 Check Fuel to Engine, Make sure there is Enough Fuel for 20min Break-In Period**
- 6 Prime Engine Oil for Minimum of 5min.** Rotate Engine over by Hand while Priming and Look for oil reaching each each rocker arm. Check for Leaks.
- 7 Insert Distributor, Double Check it is NOT 180degrees Out. Check Again for Correct Firing Order.**
- 8 Crank Engine Over and Adjust Timing**
- 9 Quick Adjust Carburetor or EFI to Run**
- 10 Allow to run for 20min at 2000-2200rpms** to Break-In Flat Tappet Cam/Lifters.
- * Keep an eye on **Engine Oil Pressure** and **Coolant Temp** during Break-In Period.
- 11 Shutdown and allow Engine to Cool.**
- 12 Re-Torque Cylinder Head Bolts.**
- 13 Adjust Valve Lash if Required.**
- 14 Drain Engine Oil & Replace Oil Filter.**
- 15 Change Engine Oil- Recommend Amsoil SAE 30 Break-In Engine Oil Again.**
- * Easy Driving for the First 500miles.
- 16 Change Engine Oil and Filter after the Initial 500miles of Engine Use**